

POWER SECTION

Model No: AT1125564.6

Revised: 9/10/2020

| Rotor Specifications | |
|----------------------|----------------------|
| | inches |
| Overall Length | 219.50 |
| Contour Length | 210.50 |
| Major Diameter | 7.498 |
| Eccentricity | 0.538 |
| Head diameter | 6.500 |
| Thread Form | 2.125-6 SA |
| Weight | 1876 lbs |
| Material | 17-4 PH ¹ |

| Stator Specifications | |
|------------------------|-----------------------|
| | inches |
| Overall Length | 230.00 |
| Tube OD | 11.25 |
| Tube ID | 9.25 |
| Rubber Cutback Top/End | 10.50 / 10.50 |
| Weight | 2385 lbs |
| Number of Stages | 4.6 |
| Tube Material | 4140/4142 Alloy Steel |
| Rubber Options | HNBR-HPT |


| HNBR-HPT High Temp ³ (in) | | Fits (+ Compression / - Loose) | | | | |
|--------------------------------------|--------------------|--------------------------------|--------|--------|--------|---------------------|
| Size | Minor ² | 75 °F | 125 °F | 175 °F | 250 °F | 300 °F ³ |
| .5 US | | | | | | |
| STD | 6.421 | 0.001 | 0.034 | 0.066 | 0.115 | 0.148 |
| .5 OS | | | | | | |
| 1.0 OS | | | | | | |
| 1.5 OS | | | | | | |
| 2.0 OS | | | | | | |
| 2.5 OS | | | | | | |

| HNBR-HPT (in) | | Fits (+ Compression / - Loose) | | | | |
|---------------|--------------------|--------------------------------|--------|--------|--------|---------------------|
| Size | Minor ² | 75 °F | 125 °F | 175 °F | 250 °F | 300 °F ³ |
| .5 US | | | | | | |
| STD | 6.421 | 0.001 | 0.034 | 0.066 | 0.115 | 0.148 |
| .5 OS | | | | | | |
| 1.0 OS | | | | | | |
| 1.5 OS | | | | | | |
| 2.0 OS | | | | | | |
| 2.5 OS | | | | | | |

| Performance Specifications | |
|----------------------------|------------|
| Flow Range (gpm) | 800 - 1800 |
| Speed Range (rpm) | 70 - 160 |
| Torque Slope (ft-lb/psi) | 31.59 |
| Rotation (rev/gal) | 0.089 |
| Off Bottom Pressure (psi) | 160 |

| Performance Details | | |
|------------------------|---------------------------------|----------|
| | HNBR-HPT High Temp ³ | HNBR-HPT |
| Max Diff Press (psi) | 460 | 920 |
| Stall Diff Press (psi) | 690 | 1450 |
| Max Torque (ft-lb) | 14540 | 29070 |
| Stall Torque (ft-lb) | 21800 | 45780 |

■ (HNBR-HPT High Temp³) ■ (HNBR-HPT) ■ Torque



¹ Coating options of chrome or tungsten carbide are available. ² Vector Gauge Readings at Room Temp 75°F. ³ HPT High Temp parameters are recommended when BHCT exceeds 300°F. BHCT exceeding 430°F will void warranty. It is recommended to run stator for no more than 15 hours at BHCT above 375°F. Performance curves are based on new rotor and stator dimensions and for reference only. Actual performance may vary depending on fit and drilling conditions. The stall torque may exceed that specified for the connected components. Operating over the recommended limits may result in damage to the power section and connected components. Please visit www.AbacoDrilling.com for the latest specification revisions.

LOCATIONS

US: Headquarters 713 Northpark Central Dr., #400 Houston, TX 77073 - Tel: (281) 869-0700 - Fax: (281) 869-0701
 US: Sales & Distribution 11308 West Interstate 20 East, Odessa, TX 79765 - Tel: (432) 248-1814
 CANADA: Stator Manufacturing 6303-39th Street Leduc, Alberta T9E 0Z3 Canada - Tel: (780) 986-8947 - Fax: (780) 986-8842
 DUBAI UAE: Stator Manufacturing Oilfields Supply Center B#57, Jebel Ali, Dubai UAE, P.O. Box 19909 - Tel: 971-4-870-8600

POWER SECTION - METRIC

Model No: AT1125564.6

Revised: 9/10/2020

| Rotor Specifications | |
|----------------------|----------------------|
| | mm |
| Overall Length | 5575.3 |
| Contour Length | 5346.7 |
| Major Diameter | 190.45 |
| Eccentricity | 13.67 |
| Head diameter | 165.10 |
| Thread Form | 2.125-6 SA |
| Weight | 851 kg |
| Material | 17-4 PH ¹ |

| Stator Specifications | |
|------------------------|--------------------------------|
| | mm |
| Overall Length | 5842.0 |
| Tube OD | 285.8 |
| Tube ID | 235.0 |
| Rubber Cutback Top/End | 267.0 / 267.0 |
| Weight | 1082 kg |
| Number of Stages | 4.6 |
| Tube Material | 4140/4142 Seamless Alloy Steel |
| Rubber Options | HNBR-HPT |


| HNBR-HPT High Temp ³ (in) | | Fits (+ Compression / - Loose) | | | | |
|--------------------------------------|--------------------|--------------------------------|-------|--------|--------|---------------------|
| Size | Minor ² | 25 °C | 75 °C | 100 °C | 125 °C | 150 °C ³ |
| .5 US | | | | | | |
| STD | 163.09 | 0.03 | 1.52 | 2.27 | 3.01 | 3.76 |
| .5 OS | | | | | | |
| 1.0 OS | | | | | | |
| 1.5 OS | | | | | | |
| 2.0 OS | | | | | | |
| 2.5 OS | | | | | | |

| HNBR-HPT (mm) | | Fits (+ Compression / - Loose) | | | | |
|---------------|--------------------|--------------------------------|-------|--------|--------|---------------------|
| Size | Minor ² | 25 °C | 75 °C | 100 °C | 125 °C | 150 °C ³ |
| .5 US | | | | | | |
| STD | 163.09 | 0.03 | 1.52 | 2.27 | 3.01 | 3.76 |
| .5 OS | | | | | | |
| 1.0 OS | | | | | | |
| 1.5 OS | | | | | | |
| 2.0 OS | | | | | | |
| 2.5 OS | | | | | | |

| Performance Specifications | |
|----------------------------|-------------|
| Flow Range (lpm) | 3030 - 6810 |
| Speed Range (rpm) | 70 - 160 |
| Torque Slope (Nm/kpa) | 6.21 |
| Rotation (rev/Liter) | 0.0235 |
| Off Bottom Pressure (kpa) | 1100 |

| Performance Details | | |
|------------------------|---------------------------------|----------|
| | HNBR-HPT High Temp ³ | HNBR-HPT |
| Max Diff Press (kpa) | 3200 | 6400 |
| Stall Diff Press (kpa) | 4800 | 10000 |
| Max Torque (Nm) | 19800 | 39500 |
| Stall Torque (Nm) | 29600 | 62100 |

■ (HNBR-HPT High Temp³) ■ (HNBR-HPT) ■ Torque



¹ Coating options of chrome or tungsten carbide are available. ² Vector Gauge Readings at Room Temp 25°C. ³ HPT High Temp parameters are recommended when BHCT exceeds 150°C. BHCT exceeding 220°C will void warranty. It is recommended to run stator for no more than 15 hours at BHCT above 190°C.

Performance curves are based on new rotor and stator dimensions and for reference only. Actual performance may vary depending on fit and drilling conditions. The stall torque may exceed that specified for the connected components. Operating over the recommended limits may result in damage to the power section and connected components. Please visit www.AbacoDrilling.com for the latest specification revisions.

LOCATIONS

| | |
|---------------------------------|---|
| US: Headquarters | 713 Northpark Central Dr., #400 Houston, TX 77073 - Tel: (281) 869-0700 - Fax: (281) 869-0701 |
| US: Sales & Distribution | 11308 West Interstate 20 East, Odessa, TX 79765 - Tel: (432) 248-1814 |
| CANADA: Stator Manufacturing | 6303-39th Street Leduc, Alberta T9E 0Z3 Canada - Tel: (780) 986-8947 - Fax: (780) 986-8842 |
| DUBAI UAE: Stator Manufacturing | Oilfields Supply Center B#57, Jebel Ali, Dubai UAE, P.O. Box 19909 - Tel: 971-4-870-8600 |