

POWER SECTION

Model No: AT650786.0

Revised: 9/24/2020

Rotor Specifications	
	inches
Overall Length	223.00
Contour Length	216.00
Major Diameter	4.52
Eccentricity	0.256
Head diameter	4.500
Thread Form	2.875 API REG
Weight	831 lbs
Material	17-4 PH ¹

Stator Specifications	
	inches
Overall Length	235.00
Tube OD	6.50
Tube ID	5.50
Rubber Cutback Top/End	8.00 / 8.00
Weight	706 lbs
Number of Stages	6.0
Tube Material	4140/4142 Alloy Steel
Rubber Options	NBR-HPW & NBR-HPO

NBR-HPW (in)		Fits (+ Compression / - Loose)				
Size	Minor ²	75 °F	125 °F	175 °F	250 °F	300 °F ³
.5 US						
STD	3.989	0.019	0.033	0.046	0.067	0.080
.5 OS	4.004	0.004	0.017	0.031	0.051	0.065
1.0 OS	4.016	-0.008	0.005	0.019	0.039	0.052
1.5 OS	4.025	-0.017	-0.004	0.010	0.029	0.043
2.0 OS	4.036	-0.028	-0.015	-0.002	0.018	0.031
2.5 OS						


NBR-HPO (in)		Fits (+ Compression / - Loose)				
Size	Minor ²	75 °F	125 °F	175 °F	250 °F	300 °F ³
.5 US						
STD	3.989	0.019	0.033	0.046	0.067	0.080
.5 OS	4.004	0.004	0.017	0.031	0.051	0.065
1.0 OS	4.016	-0.008	0.005	0.019	0.039	0.052
1.5 OS	4.025	-0.017	-0.004	0.010	0.029	0.043
2.0 OS	4.036	-0.028	-0.015	-0.002	0.018	0.031
2.5 OS						

Performance Specifications	
Flow Range (gpm)	300 - 650
Speed Range (rpm)	80 - 180
Torque Slope (ft-lb/psi)	9.06
Rotation (rev/gal)	0.270
Off Bottom Pressure (psi)	110

Performance Details		NBR-HPW	NBR-HPO
Max Diff Press (psi)		1410	1410
Stall Diff Press (psi)		2230	2230
Max Torque (ft-lb)		12780	12780
Stall Torque (ft-lb)		20120	20120

■ (NBR-HPW/HPO)

■ Torque



¹ Coating options of chrome or tungsten carbide are available ² Vector Gauge Readings at Room Temp 75°F ³ BHCT Exceeding 320°F will void warranty for NBR-HPW (325°F for NBR-HPO).

Performance curves are based on new rotor and stator dimensions and for reference only. Actual performance may vary depending on fit and drilling conditions. The stall torque may exceed that specified for the connected components. Operating over the recommended limits may result in damage to the power section and connected components. Please visit www.AbacoDrilling.com for the latest specification revisions.

LOCATIONS

US: Headquarters 713 Northpark Central Dr., #400 Houston, TX 77073 - Tel: (281) 869-0700 - Fax: (281) 869-0701
 US: Sales & Distribution 11308 West Interstate 20 East, Odessa, TX 79765 - Tel: (432) 248-1814
 CANADA: Stator Manufacturing 6303-39th Street Leduc, Alberta T9E 0Z3 Canada - Tel: (780) 986-8947 - Fax: (780) 986-8842
 DUBAI UAE: Stator Manufacturing Oilfields Supply Center B#57, Jebel Ali, Dubai UAE, P.O. Box 19909 - Tel: 971-4-870-8600

POWER SECTION - METRIC

Model No: AT650786.0

Revised: 9/24/2020

Rotor Specifications	
	mm
Overall Length	5664.2
Contour Length	5486.4
Major Diameter	114.81
Eccentricity	6.50
Head diameter	114.30
Thread Form	2.875 API REG
Weight	377 kg
Material	17-4 PH ¹

Stator Specifications	
	mm
Overall Length	5969.0
Tube OD	165.1
Tube ID	139.7
Rubber Cutback Top/End	203.0 / 203.0
Weight	320 kg
Number of Stages	6.0
Tube Material	4140/4142 Seamless Alloy Steel
Rubber Options	NBR-HPW & NBR-HPO

NBR-HPW (mm)		Fits (+ Compression / - Loose)				
Size	Minor ²	25 °C	75 °C	100 °C	125 °C	150 °C ³
.5 US						
STD	101.32	0.48	1.10	1.42	1.73	2.04
.5 OS	101.70	0.10	0.72	1.02	1.33	1.64
1.0 OS	102.01	-0.20	0.41	0.71	1.02	1.32
1.5 OS	102.24	-0.43	0.18	0.48	0.78	1.09
2.0 OS	102.51	-0.71	-0.11	0.19	0.49	0.79
2.5 OS						


NBR-HPO (mm)		Fits (+ Compression / - Loose)				
Size	Minor ²	25 °C	75 °C	100 °C	125 °C	150 °C ³
.5 US						
STD	101.32	0.48	1.10	1.42	1.73	2.04
.5 OS	101.70	0.10	0.72	1.02	1.33	1.64
1.0 OS	102.01	-0.20	0.41	0.71	1.02	1.32
1.5 OS	102.24	-0.43	0.18	0.48	0.78	1.09
2.0 OS	102.51	-0.71	-0.11	0.19	0.49	0.79
2.5 OS						

Performance Specifications	
Flow Range (lpm)	1140 - 2460
Speed Range (rpm)	80 - 180
Torque Slope (Nm/kpa)	1.78
Rotation (rev/Liter)	0.0713
Off Bottom Pressure (kpa)	770

Performance Details		
	NBR-HPW	NBR-HPO
Max Diff Press (kpa)	9800	9800
Stall Diff Press (kpa)	15300	15400
Max Torque (Nm)	17400	17400
Stall Torque (Nm)	27300	27300

■ (NBR-HPW/HPO)

■ Torque



¹ Coating options of chrome or tungsten carbide are available ² Vector Gauge Readings at Room Temp 25°C ³ BHCT Exceeding 160°C will void warranty for NBR-HPW (163°C for NBR-HPO).

Performance curves are based on new rotor and stator dimensions and for reference only. Actual performance may vary depending on fit and drilling conditions. The stall torque may exceed that specified for the connected components. Operating over the recommended limits may result in damage to the power section and connected components. Please visit www.AbacoDrilling.com for the latest specification revisions.

LOCATIONS

US: Headquarters	713 Northpark Central Dr., #400 Houston, TX 77073 - Tel: (281) 869-0700 - Fax: (281) 869-0701
US: Sales & Distribution	11308 West Interstate 20 East, Odessa, TX 79765 - Tel: (432) 248-1814
CANADA: Stator Manufacturing	6303-39th Street Leduc, Alberta T9E 0Z3 Canada - Tel: (780) 986-8947 - Fax: (780) 986-8842
DUBAI UAE: Stator Manufacturing	Oilfields Supply Center B#57, Jebel Ali, Dubai UAE, P.O. Box 19909 - Tel: 971-4-870-8600