

POWER SECTION

Model No: AT675786.0

Revised: 9/9/2020

Rotor Specifications	
	inches
Overall Length	223.00
Contour Length	216.00
Major Diameter	4.52
Eccentricity	0.256
Head diameter	4.500
Thread Form	2.875 API REG
Weight	831 lbs
Material	17-4 PH ¹

Stator Specifications	
	inches
Overall Length	235.00
Tube OD	6.75
Tube ID	5.50
Rubber Cutback Top/End	8.00 / 8.00
Weight	903 lbs
Number of Stages	6.0
Tube Material	4140/4142 Alloy Steel
Rubber Options	HNBR-HPT


HNBR-HPT High Temp ³ (in)		Fits (+ Compression / - Loose)				
Size	Minor ²	75 °F	125 °F	175 °F	250 °F	300 °F ³
.5 US						
STD	3.999	0.009	0.024	0.039	0.061	0.076
.5 OS	4.014	-0.006	0.009	0.023	0.045	0.060
1.0 OS	4.026	-0.018	-0.003	0.011	0.033	0.048
1.5 OS	4.035	-0.027	-0.012	0.002	0.024	0.038
2.0 OS	4.046	-0.038	-0.024	-0.009	0.012	0.027
2.5 OS						

HNBR-HPT (in)		Fits (+ Compression / - Loose)				
Size	Minor ²	75 °F	125 °F	175 °F	250 °F	300 °F ³
.5 US						
STD	3.999	0.009	0.024	0.039	0.061	0.076
.5 OS	4.014	-0.006	0.009	0.023	0.045	0.060
1.0 OS	4.026	-0.018	-0.003	0.011	0.033	0.048
1.5 OS	4.035	-0.027	-0.012	0.002	0.024	0.038
2.0 OS	4.046	-0.038	-0.024	-0.009	0.012	0.027
2.5 OS						

Performance Specifications	
Flow Range (gpm)	300 - 650
Speed Range (rpm)	80 - 180
Torque Slope (ft-lb/psi)	9.06
Rotation (rev/gal)	0.270
Off Bottom Pressure (psi)	110

Performance Details		
	HNBR-HPT High Temp ³	HNBR-HPT
Max Diff Press (psi)	600	1200
Stall Diff Press (psi)	900	1890
Max Torque (ft-lb)	5440	10880
Stall Torque (ft-lb)	8160	17130

■ (HNBR-HPT High Temp³) ■ (HNBR-HPT) ■ Torque



¹ Coating options of chrome or tungsten carbide are available. ² Vector Gauge Readings at Room Temp 75°F. ³ HPT High Temp parameters are recommended when BHCT exceeds 300°F. BHCT exceeding 430°F will void warranty. It is recommended to run stator for no more than 15 hours at BHCT above 375°F. Performance curves are based on new rotor and stator dimensions and for reference only. Actual performance may vary depending on fit and drilling conditions. The stall torque may exceed that specified for the connected components. Operating over the recommended limits may result in damage to the power section and connected components. Please visit www.AbacoDrilling.com for the latest specification revisions.

LOCATIONS

US: Headquarters 713 Northpark Central Dr., #400 Houston, TX 77073 - Tel: (281) 869-0700 - Fax: (281) 869-0701
 US: Sales & Distribution 11308 West Interstate 20 East, Odessa, TX 79765 - Tel: (432) 248-1814
 CANADA: Stator Manufacturing 6303-39th Street Leduc, Alberta T9E 0Z3 Canada - Tel: (780) 986-8947 - Fax: (780) 986-8842
 DUBAI UAE: Stator Manufacturing Oilfields Supply Center B#57, Jebel Ali, Dubai UAE, P.O. Box 19909 - Tel: 971-4-870-8600

POWER SECTION - METRIC

Model No: AT675786.0

Revised: 9/9/2020

Rotor Specifications	
	mm
Overall Length	5664.2
Contour Length	5486.4
Major Diameter	114.81
Eccentricity	6.50
Head diameter	114.30
Thread Form	2.875 API REG
Weight	377 kg
Material	17-4 PH ¹

Stator Specifications	
	mm
Overall Length	5969.0
Tube OD	171.5
Tube ID	139.7
Rubber Cutback Top/End	203.0 / 203.0
Weight	410 kg
Number of Stages	6.0
Tube Material	4140/4142 Seamless Alloy Steel
Rubber Options	HNBR-HPT


HNBR-HPT High Temp ³ (in)		Fits (+ Compression / - Loose)				
Size	Minor ²	25 °C	75 °C	100 °C	125 °C	150 °C ³
.5 US						
STD	101.57	0.23	0.91	1.25	1.59	1.93
.5 OS	101.96	-0.15	0.52	0.86	1.19	1.53
1.0 OS	102.26	-0.46	0.21	0.54	0.88	1.21
1.5 OS	102.49	-0.69	-0.02	0.31	0.64	0.97
2.0 OS	102.77	-0.97	-0.31	0.02	0.35	0.68
2.5 OS						

HNBR-HPT (mm)		Fits (+ Compression / - Loose)				
Size	Minor ²	25 °C	75 °C	100 °C	125 °C	150 °C ³
.5 US						
STD	101.57	0.23	0.91	1.25	1.59	1.93
.5 OS	101.96	-0.15	0.52	0.86	1.19	1.53
1.0 OS	102.26	-0.46	0.21	0.54	0.88	1.21
1.5 OS	102.49	-0.69	-0.02	0.31	0.64	0.97
2.0 OS	102.77	-0.97	-0.31	0.02	0.35	0.68
2.5 OS						

Performance Specifications	
Flow Range (lpm)	1140 - 2460
Speed Range (rpm)	80 - 180
Torque Slope (Nm/kpa)	1.78
Rotation (rev/Liter)	0.0713
Off Bottom Pressure (kpa)	770

Performance Details		
	HNBR-HPT High Temp ³	HNBR-HPT
Max Diff Press (kpa)	4200	8300
Stall Diff Press (kpa)	6200	13100
Max Torque (Nm)	7400	14800
Stall Torque (Nm)	11100	23300

■ (HNBR-HPT High Temp³) ■ (HNBR-HPT) ■ Torque



¹ Coating options of chrome or tungsten carbide are available. ² Vector Gauge Readings at Room Temp 25°C. ³ HPT High Temp parameters are recommended when BHCT exceeds 150°C. BHCT exceeding 220°C will void warranty. It is recommended to run stator for no more than 15 hours at BHCT above 190°C.

Performance curves are based on new rotor and stator dimensions and for reference only. Actual performance may vary depending on fit and drilling conditions. The stall torque may exceed that specified for the connected components. Operating over the recommended limits may result in damage to the power section and connected components. Please visit www.AbacoDrilling.com for the latest specification revisions.

LOCATIONS

US: Headquarters	713 Northpark Central Dr., #400 Houston, TX 77073 - Tel: (281) 869-0700 - Fax: (281) 869-0701
US: Sales & Distribution	11308 West Interstate 20 East, Odessa, TX 79765 - Tel: (432) 248-1814
CANADA: Stator Manufacturing	6303-39th Street Leduc, Alberta T9E 0Z3 Canada - Tel: (780) 986-8947 - Fax: (780) 986-8842
DUBAI UAE: Stator Manufacturing	Oilfields Supply Center B#57, Jebel Ali, Dubai UAE, P.O. Box 19909 - Tel: 971-4-870-8600